

# VESTA® COMMERCIAL

# **VESTA®** Filtration Solutions

YOUR BUSINESS, YOUR CUSTOMERS & YOUR WATER



#### **VESTA COMMERCIAL FILTRATION SOLUTIONS**



VESTA Filtration Systems are designed for commercial and industrial applications requiring treated water for turbidity removal, iron removal, or taste and odor control, at flow rates up to 625 GPM. With a wide variety of filter media available, we can manufacture to unique specifications in single or a variety of multiple tank systems to meet your specific requirements. With our dedication, you can be assured that VESTA will provide you with the support you deserve.



### **VESTA 1-1/2" CONTROL**

- 1-1/2" Top Mount or Side Mount Control Valve for commercial & industrial applications
- Flow Rates up to 70 GPM per service vessel

#### WATER QUALITY MAKES A DIFFERENCE

VESTA Filtration Systems are always custom designed and built for each and every client to provide years of trouble-free service, even in the most demanding applications. By sizing and matching the control valve, pressure vessel(s), and media, the removal of many unwanted minerals, chemicals, tastes, and odors or bacteria can effectively be achieved. These systems can be combined and used as pre-treatment or post-treatment to additional water treatment systems or can be used as a stand-alone water treatment solution.

FILTER-AG PLUS® FILTERS - Filter-Ag Plus® is a unique natural ore called clinoptilolite with many outstanding advantages over typical granular filter sands and multimedia used for suspended solids reduction. The granules are angular in shape, with rough surfaces and microporous void spaces. This creates a surface area over 100 times greater than silica sand. The angularity of the granules and the tapered internal pore spaces allow for reduced dirt, silt, and organic matter suspended in water by bridging, straining, and adhesion. The rough surface and internal porosity provide a high surface area for efficiently reducing suspended matter. Deep bed filtration can reduce suspended solids to the 5-micron or less range.

ACTIVATED CARBON SYSTEMS are best for removing chlorine, dissolved organic contaminants, tannins, color, phenols, and unpleasant tastes and odors. The activation process of carbon determines what adsorption and filtering characteristics the carbon will possess, as well as determine what can be filtered out of the water. The availability of numerous varieties of carbons today makes activated carbon filters a versatile solution for a wide variety of water problems.

IRON FILTERS - Manganese Greensand filters provide excellent removal of iron and manganese. Manganese greensand is a purple-black filter medium that removes soluble iron, manganese, and hydrogen sulfide from water supplies. As the water passes through the filter, the media oxidizes and traps any iron and manganese present. Backwashing and rinsing of the media remove the contaminants.

#### **CONTROL VALVE KEY FEATURES**

- Top or side mount control valve suited for commercial/industrial applications
- Epoxy coated lead free brass construction -Certified to NSF/ANSI 61 AND 372
- + Service flows up to 125 gpm with backwash rates to 85 gpm (single tank systems, higher flows with multi tank systems)
- Solid state microprocessor with easy access front panel settings
- Front panel display for time of day, days until next regeneration, volume remaining, current flow rate and total volume used (Totalizer)
- Methods to initiate regeneration; meter immediate, meter delayed, time clock delayed
- Optional double backwash feature offers optimum regeneration, cleaning ability and efficiency
- Fully adjustable cycle times with 6-cycle control delivers controlled backwash, down-flow brining/ slow rinse, second backwash, fast rinse, refill and down-flow service
- Coin Cell Lithium battery back-up with an 8 hour carry over
- + 15-volt AC Adapter, safe & easy installation
- Built-in progressive flow, up to 4 tanks







3" & Larger Solutions

## **VESTA LARGE COMMERCIAL**

Each VESTA Commercial system is designed specifically for each application. The VESTA 3" control valve provides flow rates up to 250 GPM for a single tank application.

Does your application require more than 250 GPM? We can manufacture to unique specifications, single or a variety of multiple tank systems to meet your specific requirements. We custom tailor your system to provide you with the convenience you want while giving you the performance and durability you need for all of your individual application requirements.

A variety of configurations are available, ASME code tanks in composite or steel can be specified when required, and can be custom designed to meet your specific application requirements.

Each system is fully customized to your specs, ask your VESTA Professional Dealer what they can do for you.



#### YOUR AUTHORIZED VESTA DEALER:



